

Electrical Conductivity Meter AP-2

Special Features:

- Measures electrical conductivity (EC) and temperature.
- Automatic Temperature Compensation (ATC)
- Water-resistant housing
- Measurement Range: 0-9999 μ S
- Digital Calibration (push button)
- Auto-off function, data-hold function and low-battery indicator.
- Display: large and easy-to-read LCD screen includes simultaneous temperature reading.
- Factory Calibrated: The AP-2 is calibrated with a 700 μ S solution.
- The meter can be recalibrated with digital calibration using the push buttons, rather than a screwdriver.
- Includes a cap and batteries



Applications:

AP-2 series, a line of handheld TDS/EC meters with a sleek design that's perfect for today's modern laboratories. The AP-2 digital water testers are the next generation for today's tech-savvy and health-conscience consumer.

Performance Specifications:

EC Range	: 0-9999 μ S
Temperature Range	: 0-80 $^{\circ}$ C; 32-176 $^{\circ}$ F
Resolution	: 1S; Temp. resolution is 0.1 $^{\circ}$ C/F
Accuracy	: +/- 2%
Calibration	: Digital calibration by push button.
Housing	: Water-resistant
Power source	: 1 x 3V button cell (included) (model CR2032)
Dimensions	: 15 x 2.8 x 1.3 cm (5.9 x 1.1 x 0.5 inches)
Weight	: 42.5 g (1.5 oz)

