

Multi Parameter 6 in 1 Water Quality Monitor

Special Features:

- 6 Meters In 1 Instrument
- Large Dual Level Back Lit LCD Display
- Wall Mounting For Continuous Monitoring
- Rechargeable Batteries With Battery Charger
- Precise And Immediate Detection Of PH Changes
- Economical And User Friendly



Description:

PHT-028 combines 6 meters into one easy to use wall mounting continuous monitor. Featuring a large, dual-level, back-lit LCD display the meter can display the EC/TDS/CF of your solution together with the choice of either pH, temperature or Oxidation-Reduction Potential (ORP). Precision pH monitor immediately detects changes in solution pH. With a 6 V DC power supply included with the meter (also included rechargeable battery). This instrument features BNC composite electrode making it easier in the world to facilitate the replacement of used electrodes.

Performance Specifications:

Measuring Range

PH	0.00 - 14.00 PH
Temperature	-50°C - 70°C
EC	00.00 - 19.99 EC
CF	0.0 - 199 CF
TDS	10 - 19990 ppm
ORP	0 - 1999 mV

Resolution

PH	0.01 PH
Temperature	0.1°C
EC	0.01 EC
CF	0.1 CF
TDS	10 ppm
ORP	1 mV

Accuracy

PH	±0.05
Temperature	±1°C
EC	±2% of F.S
CF	±2% of F.S
TDS	±2% of F.S
ORP	±0.1% of F.S ± 1 digit

*	PH	:	Potential of Hydrogen
	EC	:	Electrical Conductivity
	CF	:	Conductivity Factor
	TDS	:	Total Dissolved Solids
	ORP	:	Oxidation Reduction Potential