

Universal Process Indicator for Panel Mounting

Features:

- 5 Digits
- TC / RTD / mV / Current / Voltage Inputs
- Easy to Use
- 7 Segment LED Display (Red)
- 24V Auxiliary Power Supply (Optional)
- Size: 48 x 96MM



Specifications:

Digits	: 5 Digit, 7 Segment LED Display
Display Height	: 0.56"
Inputs	: Thermocouple (J / K / T / R / S) RTD (Pt-100) DC Analog Inputs (-5 to 56 mV / 0 to 10 V / 4 - 20mA / 0 - 20mA)
Resolution	: 1° / 0.1° for TC / RTD Only Fixed Resolution: 1° for R / S Type TC 1 / 0.1 / 0.01 / 0.001 for Analog Inputs
Temperature Units	: C / F Selectable
Indication Accuracy	: ±0.25% ± 1° (TC Inputs) ±0.1% ± 1° (RTD Inputs) ±0.5% ± 1 (Analog Inputs)
Auxiliary Power	: 24V DC, 30 mA
Supply Voltage	: 85 to 270V AC / DC (50 / 60Hz) 24VDC (Optional Supply)
Temperature	: 0 to 50°C (Operating) -20 to 75°C (Storage)
Weight	: 200 gms
Protection	: IP65 (Faceplate)
Housing	: Fireproof ABS Enclosure

Dimensions & Wiring Drawing:

